



TECNET P260 | Professional FM Transceiver

Main Functions

- VOX
- SOS
- Scan
- 1750HZ
- Scrambler
- Compandor
- Battery Save
- Tail Elimination
- Frequency UHF 400-520MHz/VHF 136-174MHz
- 16 Channels
- Battery Report
- High/Low Power
- PC Programmable
- Wide/Narrow Band
- SK Programmable
- Chinese/English Voice Report
- CTCSS/DCS Support Non-standard

CTCSS/DCS Support Non-standard

- SOS
- Scan
- Tail Elimination
- Wide/Narrow Band
- Battery Save
- Scrambler
- Battery Report
- SK Programmable
- PC Programmable
- Compandor
- High/Low Power
- Chinese/English Voice Report

Technical Specification

GENERAL		TRANSMITTER		RECEIVER	
Frequency Range	UHF: 400-520MHz 200-260 MHz VHF: 136-174MHz	Output Power	H:10W ±1W L:5W ±1W	Reference Sensitivity	122dBm
RF Output Power	H:10W ± 1W L:5W ±1W	Modulation	F3E	Adjacent Channel Selectivity	≥65 dB
Channels	16	Modulation Sensitivity	12±5mV	Inter-modulation	-55dB
Channel Spacing	25Khz 12.5Khz	Adjacent Channel Power	≤-65dB (WIDE) ≤-55 dB(Narrow)	S/N	≥50 dB (WIDE) ≤-40 dB (Narrow)
CTCSS/DCS	50 CTCSS/ 105 DCS	Modulation Distortion	≤ 5%	Rated Output Power	≤1W
Antenna Impedence	50 Ω			Rated Audio Distortion	≤10%
Operating Temperature	-20℃ + 50℃				
Operating Voltage	DC 7.4V				
Battery Type	2800mAh Li-ion				
Dimension (excluding antenna)	132(H) x 61(W) x 43(D)mm				
Weight (Battery Antenna Included)	Approx. 280g				

Standard Accessories



Antenna



Battery



Charger



Adapter



Belt clip